Choosing tiles for the job

Compare intended use, installation and verified performance.

Build Supply | SulfRock | Intelligent Panel Systems | HomePod

1 Wall or floor

Confirm the product is intended for the proposed location and loading. A wall tile is not automatically a floor tile.

2 Wet and external areas

Check water absorption, frost suitability and the complete waterproofing/detailing strategy.

3 Slip risk

Specify suitable slip performance for expected water, contamination, footwear and use. Finish appearance alone is insufficient.

4 Substrate compatibility

Select the adhesive, grout, preparation and movement joints for the substrate and tile.

5 Layout and supply

Check size variation, batch shade, wastage and availability for repairs before ordering.

6 Tile or brick slip

Brick slips are a separate cladding selection. Confirm system adhesive, jointing, support, exposure and fire evidence.

Before ordering: confirm the tile or brick-slip system, substrate, exposure and installation detail.

REFERENCE GUIDANCE

GOV.UK: Approved Documents (England)
HSE: construction dust controls

Use current product instructions and the approved project design. For regulations, confirm the UK nation, applicable edition and transitional arrangements.

Help us keep our information accurate.

If you notice an error, outdated information or something that needs clarification in this document, please let us know.
Report an Issue: Visit our website and select Report a Website or Document Issue.
intelligentpanelsystems.co.uk