Facade glazing: combine the properties

Treatments, coatings and glazing units can be combined.

Build Supply | SulfRock | Intelligent Panel Systems | HomePod

1 Safety and retention

Specify the required impact safety and post-breakage behaviour. Toughened and laminated glass serve different purposes.

2 Thermal performance

Compare glass and whole-window/facade performance separately, including frames and edge effects.

3 Solar control

Balance solar heat gain, daylight, glare and appearance. Low-E and solar-control coatings are not interchangeable.

4 Acoustics

Specify tested glazing configurations for the noise spectrum and facade requirements.

5 Pattern and privacy

Tint, reflective coatings and ceramic frit affect light and appearance; they do not automatically establish safety performance.

6 Engineer the assembly

Check wind loads, support, seals, thermal stress, fire requirements and replacement access.

Specify a complete glazing configuration and supporting test data, rather than choosing one category label.

REFERENCE GUIDANCE

GOV.UK: Approved Documents (England)

Use current product instructions and the approved project design. For regulations, confirm the UK nation, applicable edition and transitional arrangements.

Help us keep our information accurate.

If you notice an error, outdated information or something that needs clarification in this document, please let us know.
Report an Issue: Visit our website and select Report a Website or Document Issue.
intelligentpanelsystems.co.uk